



General Description




AFN9875S, N-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent $R_{DS(ON)}$, low gate charge.

These devices are particularly suited for low voltage power management, and low in-line power loss are needed in commercial industrial surface mount applications.

Features

- 80V/40A, $R_{DS(ON)} = 9.8m\Omega @ V_{GS} = 10V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- TO-252-2L package design

Pin Description (TO-252-2L)



Application

- Motor and Load Control
- Power Management in White LED System
- Push Pull Converter
- LCD TV Inverter & AD/DC Inverter Systems.

Pin Define

Pin	Symbol	Description
1	G	Gate
2	S	Source
3	D	Drain

Ordering Information

Part Ordering No.	Part Marking	Package	Unit	Quantity
AFN9875ST252RG	9875S	TO-252-2L	Tape & Reel	2500 EA

- ※ A Lot code
- ※ B Date code
- ※ AFN9875ST252RG : 13" Tape & Reel ; Pb- Free ; Halogen- Free



Absolute Maximum Ratings

(T_A=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	80	V
Gate –Source Voltage	V _{GSS}	±25	V
Continuous Drain Current(T _J =150°C)	I _D	T _A =25°C	40
		T _A =70°C	30
Pulsed Drain Current	I _{DM}	60	A
Continuous Source Current(Diode Conduction)	I _S	40	
Power Dissipation	P _D	T _A =25°C	40
		T _A =70°C	15
Operating Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{STG}	-55/150	°C
Thermal Resistance-Junction to Ambient	R _{θJA}	62.5	°C/W


Electrical Characteristics

(T_A=25°C Unless otherwise noted)


Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250uA	80	83		V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	2.0	3.0	4.0	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =64V, V _{GS} =0V			1	uA
		V _{DS} =64V, V _{GS} =0V T _J =85°C			30	
On-State Drain Current	I _{D(on)}	V _{DS} ≥ 10V, V _{GS} =10V	75			A
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =10V, I _D =40A		7.8	9.8	mΩ
Forward Transconductance	g _{FS}	V _{DS} =15V, I _D =30A		55		S
Diode Forward Voltage	V _{SD}	I _S =30A, V _{GS} =0V		0.8	1.5	V
Dynamic						
Total Gate Charge	Q _g	V _{DS} =40V, V _{GS} =10V I _D ≡15A		69	90	nC
Gate-Source Charge	Q _{gs}			18		
Gate-Drain Charge	Q _{gd}			20		
Input Capacitance	C _{iss}	V _{DS} =30V, V _{GS} =0V f=1MHz		3480		pF
Output Capacitance	C _{oss}			410		
Reverse Transfer Capacitance	C _{rss}			200		
Turn-On Time	t _{d(on)}	V _{DD} =38V, R _L =3.1Ω I _D ≡12.5A, V _{GEN} =10V R _G =1.0Ω		25	45	ns
	t _r			15	30	
Turn-Off Time	t _{d(off)}			35	60	
	t _f			10	20	




Typical Characteristics




Output Characteristics




Transfer Characteristics




Transconductance



On-Resistance vs. Gate-to-Source Voltage vs. Temperature




On-Resistance vs. Drain Current




Capacitance




Typical Characteristics




On-Resistance vs. Junction Temperature




Threshold Voltage



Gate Charge



Drain Source Breakdown vs. Junction Temperature




Normalized Thermal Transient Impedance, Junction-to-Case




Typical Characteristics


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching Test Circuit & Waveforms





Package Information (TO-252-2L)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
c	0.430	0.580	0.017	0.023
c1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP.		0.091 TYP.	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
L3	0.600	0.900	0.024	0.035
V	3.800 REF.		0.150 REF.	

©2010 Alfa-MOS Technology Corp.
2F, No.80, Sec.1, Cheng Kung Rd., Nan Kang Dist., Taipei City 115, Taiwan (R.O.C.)
Tel : 886 2) 2651 3928
Fax : 886 2) 2786 8483
©http://www.alfa-mos.com